


SWINGING FIRE HOSE REEL AND MODLUAR CABINET MOUNTED AS SINGLE OR CABINET WITH PLACE FOR EXTINGUISHER IN WITH HORIZONTAL/ VERTICAL POSITION. WALL-MOUNTING OR RECESS-MOUNTING.

Cabinet for indoor use in office buildings, schools, hospitals, kindergartens, sports arenas, cinemas, hotels and conference centres, airports and shopping centres.







Cabinet with <u>horizontal</u> extinguisher place (K) for wall or recess mounting



Cabinet with <u>vertical</u> extinguisher place (KP) for wall or recess mounting

Model	Hose length [m]		Dimensions [mm]	
Woder	DN19	DN25	WxHxD	
HW-19N/W-20	20		780x780x180	
HW-19N/W-25	25		780x780x180	
HW-19N/W-30	30		780x780x180	
HW-25N/W-20		20	780x780x180	
HW-25N/W-25		25	780x780x180	
HW-25N/W-30		20	780x780x180	

Model	Hose length [m]		Dimensions [mm]			
Model	DN19	DN25	W1 x H x D			
HW-19N/W-K-20	20		1010x780x180			
HW-19N/W-K-25	25		1010x780x180			
HW-19N/W-K-30	30		1010x780x180			
HW-25N/W-K-20		20	1010x780x180			
HW-25N/W-K-25		25	1010x780x180			
HW-25N/W-K-30		20	1010x780x180			

or recess mounting							
Model		Hose length [m]		Dimensions [mm]			
	Wodel	DN19	DN25	W x H1 x D			
	HW-19N/W-KP-20	20		780x1010x180			
	HW-19N/W-KP-25	25		780x1010x180			
	HW-19N/W-KP-30	30		780x1010x180			
	HW-25N/W-KP-20		20	780x1010x180			
	HW-25N/W-KP-25		25	780x1010x180			
	HW-25N/W-KP-30		20	780x1010x180			

## GRAS basic set HW-19/25N/W-K/KP-20/30 supplied with:

- · Hose reel with side discs powder coated RAL 3000 red (gloss 80)
- · Hose reel centre parts made of brass
- · DN25 (1") manual stop valve
- · GRAS jet/spray/shut-off nozzle
- Black hose, designed to standard EN694 for fire hose reels standard
- Supply hose,
- · Cabinet body made of galvanised steel
- Door catch/release handle with plastic breakable window

- Gras Hinges System right or left hand side opening system changeable by user
- · Ø45 mm knockouts for inlet pipework on 3 sides
- · Cabinet powder coated RAL 9010 white gloss 80 standard
- · Door opening 180°
- · Installation instructions
- · Marking acc. to EN 671
- EC (CE) certificate of conformity no.: 1438/CPD/0004, 1438/CPD/0003
- Cabinet made in accordance to EN 12944 corrosion protection level C1

## Options:

- · Cabinet color RAL 3000 red gloss 80
- Other cabinet RAL color \_\_\_\_\_\_
- · Light fire hose
- Gras Easy Frame adjustable frames for recess mounting (4pcs set) separate for Single, and K (horizontal), KP vertical) model
- Extended supply hose with steel spring for bottom water supply
- Modular Extinguisher Cabinet to make a cabinet with horizontal extinguisher place (K) or to make a cabinet with vertical extinguisher place (KP)