

Manufacturer:
KZWM OGNIОCHRON S.A.
ul. Krakowska 83c, 34-120 Andrychów, Poland
Phone +48 33 875 10 70, Fax +48 33 875 10 77
e-mail: export@ogniochron.eu

www.ogniochron.eu

ogniochron
KZWM OGNIОCHRON S.A.

Application

Applicable in paint shops, power industry, industrial halls and everywhere where usage of extinguishing powders is not recommended due to presence of devices sensitive to dust and impurities. The extinguisher does not leave any remains after application.



Basic features

- Easy and ergonomic operation.
- Long hose with a snow horn at the end makes extinguishing easier.
- New generation of light, steel cylinder.
- Economical maintenance and service.
- Valve equipped with bursting disc.
- Construction of the valve enables temporary interruption of extinguishing.
- For extinguishing of fire type C.
- Cylinder of extinguisher covered with polyester paint, resistant to UV radiation.


Quality and safety

Manufactured according to requirements of domestic and EU markets on the basis of certified quality system ISO 9001. Fulfills requirements of European Standard EN3 and Safety Directive PED 97/23/EC.



Technical data

Extinguishing efficiency	55 B
Weight of extinguishing agent	5 kg
Operation time	9 s
Cylinder test pressure	320 bar
Operating temperature	-20 °C / +60 °C
Total weight	14 kg
Fire under voltage	1000 V or 123000 V*
Total height (A)	660 mm
Cylinder diameter (B)	140 mm



*Extinguisher GS-5x B/E enables extinguishing of electric devices under voltage up to 123000 V

Carbon dioxide extinguisher

GS-5x B

GS-5x B/E*

