

LED Flashlight M-FIRE 03 for use in hazardous locations

Product code: PHH0012



Specification:

Batteries included:	✓
Operation time:	100% - 6h 10min; 45% - 13h
Light output:	157 lm
ATEX NO.:	ATEX No.: II 1 G Ex ia IIC T4 IP67 DEMKO 13 ATEX 1205039X Rev. 3
Operation modes:	100%; 45%
Weight with batteries:	240g
Waterproof:	IP67
Dimensions:	172 × 47 × 47 mm
Light Distance:	117m
Power supply:	4 x AA
Light source:	Cree® XP-G2
UP Light output:	157 lm
UP Light source:	Cree® XP-G2
UP Power supply:	4 x AA
UP Operation time:	6h 10min
	: 240

Product description

Firefighters and professionals requiring reliable lighting to do their courageous jobs in hazardous locations depend on the M-Fire 03 intrinsically safe (Ex ATEX) industrial flashlight. To prevent sparks generated by an accidental opening, a screw secures the flashlight's head. A built-in pressure valve releases heat, keeping the flashlight's internal parts from dangerously overheating. Despite its helmet-friendly lightweight, the M-Fire 03 is shock, dust and water resistant boasting an IP67 ANSI rating. A magnetic control switch easily engages the lights 157 lms. A safety lock prevents battery drainage while in transport, ensuring the light's 13-hour operation time is always available when needed.

