



SWINGING FIRE HOSE REEL AND CABINET FOR WALL-MOUNTING OR RECESS-MOUNTING

For indoor use in office buildings, schools, hospitals, kindergartens, sports arenas, cinemas, hotels and conference centres, airports and shopping centres.

DN 19/25

Model	Hose length [m]		Dimensions [mm] W x H x D
	DN19	DN25	
HW-19N/W-20	20		795x795x110
HW-19N/W-25	25		600x600x150
HW-19N/W-30	30		795x795x110
HW-25N/W-20		20	795x795x150
HW-25N/W-30		30	795x795x150
HW-25N/W-20		20	780x780x180
HW-25N/W-30		30	780x780x180

GRAS basic set HW-19/25N/W-20/30 supplied with:

- Hose reel with side discs powder coated RAL 3000 red (gloss 80)
- Hose reel centre parts made of brass
- DN25 (1") manual stop valve
- GRAS jet/spray/shut-off nozzle
- Black hose, designed to standard EN694 for fire hose reels - *standard*
- Supply hose DN25 (1")
- Cabinet body made of galvanised steel
- Door catch/release handle with plastic breakable window
- **Gras Hinges System** - right or left hand side opening system changeable by user
- Ø45 mm knockouts for inlet pipework on 3 sides
- Cabinet powder coated RAL 9010 white gloss 80 - *standard*
- Door opening - 180°
- Installation instructions
- Marking acc. to EN 671
- EC (CE) certificate of conformity no.: 1438/CPR/0063; 1438/CPR/0062; 1438/CPR/0004; 1438/CPR/0003
- Cabinet made in accordance to EN 12944 corrosion protection level C1

Options:

- Cabinet color RAL 3000 red gloss 80
- Other cabinet RAL color _____
- Light fire hose
- **Gras Easy Frame** - adjustable frames for recess mounting (4pcs set)