

Manufacturer:
KZWM OGNIОCHRON S.A.
ul. Krakowska 83c, 34-120 Andrychów, Poland
Phone +48 33 875 10 70, Fax +48 33 875 10 77
e-mail: export@ogniochron.eu

www.ogniochron.eu

ogniochron
KZWM OGNIОCHRON S.A.

Przeznaczenie

Extinguishing device designed for extinguishing of devices sensitive to dust and impurities. Special design of nozzle eliminates the phenomenon of thermal shock. Particularly recommended for protection of electronic devices, including computers, switching stations and control boards, server rooms etc. This device does not leave any residue of extinguishing agent.



Podstawowe cechy

- Easy and ergonomic operation.
- Safe for electronic devices (eliminated phenomenon of thermal shock).
- New generation of light, steel cylinder.
- Economical maintenance and service.
- Valve equipped with bursting disc.
- Construction of the valve enables temporary interruption of extinguishing.
- Cylinder of extinguisher covered with polyester paint, resistant to UV radiation.

Jakość i bezpieczeństwo


Safe for electronic devices (eliminated phenomenon) of thermal shock caused by application of carbon dioxide (normal carbon dioxide extinguishers) and has a positive opinion of The Main School of Fire Service (SGSP) in Warszawa.

CE
0062



Dane techniczne

Weight of extinguishing agent	2 kg
Working agent	CO ₂
Operation time	6 s
Cylinder test pressure	250 bar
Operating temperature	-20 °C / +60 °C
Total weight	~6,5 kg
Fire under voltage	1000 V
Total height	543 mm
Cylinder diameter	105 mm



Extinguishing device

GSE-2x

