

MODEL: VST-C588H *DC Operated Carbon Monoxide Alarm With Hush Feature*
Version:A0

FEATURES AND BENEFITS



- ▶ DC operated carbon monoxide alarm
- ▶ Non-radioactive technology for environmental friendly
- ▶ CO concentration threshold:
varying time-to-alarm depending on concentration
- ▶ With quick fix mounting bracket for easy installation
and simple AC connector for easy installation
- ▶ Fitting and battery tamper resist feature
- ▶ LED indicator
- ▶ Low-battery warning indicator
- ▶ Hush/Test button
- ▶ Auto-reset when CO clears
- ▶ CE approved, comply with EN50291,
UL 2034 standard

PRODUCT SPECIFICATIONS

Model Number	VST-C588H
Power Source	9V DC Battery
Electrical Rating	BATTERY Operating voltage : 9VDC Operating current (Max.): 30uA (standby); 30mA (alarm)
Response Times	At 50 ppm, unit must alarm within 60 ~ 90 min At 100 ppm, unit must alarm within 10 ~ 40 min At 300 ppm, unit must alarm within 3 min
Maximum Hush Time	4 min
Alarm Sound Level	85 decibels at 1 meters
Detection Type	Electrochemical
Operation Temperature	5°C to 38 °C
Ambient Humidity	15% to 90% Relative Humidity

SHIPPING SPECIFICATIONS

Model Number	VST-C588H
Unit Dimension	
Master Ctn. Quantity	
Master Ctn. Dimension	
Master Ctn. Weight	

Xiamen Vs-Top Electronics Co., Ltd.

6th floor, JinZhongDa Park, No.666 Yangguang Road, XinYang Industrial District,
 Haicang, Xiamen, China 361028

Tel: +86-592-6017700 Fax: +86-592-6017711

E-mail: sales@orientalert.com Website: www.orientalert.com