

Heat Alarm

MODEL: VST-H598I

V-DSH-009A(A0)

Interconnectable Fixed Temperature Heat Alarm

FEATURES AND BENEFITS



- AC/ DC Operated Fixed Temperature Heat Alarm
 Sensitive only to a fixed temperature-
- Less nuisance alarms due to contamination, dust and insects
- With quick fix mounting bracket and simple AC connector for easy installation
- ► Fitting and battery tamper resist feature
- ►Alarm Point: 58°C(135°F) fixed temperature triggers alarm
- Alarm and AC power indicator
- Low-battery and battery missing warning indicator
 Self-test button
- ▶Interconnectable (Up to 40 Heat And/Or Smoke Alarms)
- ► CE, FCC approved, comply with EN54, EN50130-4, UL521 standard

PRODUCT SPECIFICATIONS

Model Number	VST-H598I
Operation Temperature	-23 °C to 70°C
Power Source	220-240V AC 50Hz with 9V(6F22) battery back-up (battery included)
Alarm Point	58 $^\circ \mathrm{C}(135^\circ \mathrm{F})$ fixed temperature triggers alarm
Battery Back-up Life	In the event off a break in the mains supply the battery will give detector operation for 1 year minimum
Operation Current	<20mA operation(mains)
Alarm Sound Level	85 decibels at 3m(10 ft)
Recommended Coverage	232 m ² (2500 square feet)
Recommended Spacing	15m (50 feet)
Maximum Distance From Wall	7.5m (25 feet)

SHIPPING SPECIFICATIONS

Model Number	VST-H598I
Unit Dimension	11.2cm x 11.2cm x 4.7 cm
Master Ctn. Quantity	100
Master Ctn. Dimension	62cm x27cm x38cm
Master Ctn. Weight	24.00 Kgs

INSTALLATION

For interconnecting line, only use #14-#18 AWG minimum solid or stranded wire. When being interconnected, maximum wire length between any two is 1500 feet for #18 AWG or 4000 feet for #14 AWG (20 OHMS loop resistance). This heat alarm can be interconnected with as many as 40 other DC or AC ORIENTALERT heat alarms and/or smoke alarms. Do not connect to any other type or model heat alarms except the ones we specify. And this heat alarm is powered by 220-240V AC 50Hz and with 9V DC Battery back-up.



