

Smoke Alarm

V-DSH-008E(A0)

MODEL: VST-IS588IH Interconnectable Ionization Smoke Alarm

FEATURES AND BENEFITS



- ▶ Battery Operated Ionization Type Smoke Alarm
- ▶lonization sensor for fast flaming fires
- ▶Insects Proof
- ▶ Hush feature
- High and stable sensitivity
- ►With quick fix mounting bracket and simple connector for easy installation
- Fitting and battery tamper-resist feature
- Inter-connectable up to 40 units
- ▶LED Alarm indicator
- Low-battery and battery missing warning indicator
- ▶Self-test button
- Auto-reset when smoke clears
- ▶CE, BSI, SAI Global approved, comply with EN14604, AS3786 and UL217 standard

PRODUCT SPECIFICATIONS


Model Number	VST-IS588IH
Detection Type	Ionization Chamber
Operation Temperature	4°C~38°C
Power Source	9V Battery
Battery Life	1 year minimum
Operation Current	<30mA operation (in alarm)
Alarm Sound Level	85 dB at 3m(10 feet)
Ambient Humidity	10%~90%
Interconnect Facility	40 smoke detectors and /or heat detectors 150m maximum
Sensitivity to smoke	0.61 ~ 1.92 %/FT.OBS.


SHIPPING SPECIFICATIONS


<u> </u>	
Model Number	VST-IS588IH
Unit Dimension	11.6cm x 11.6cm x 4.7cm
Master Ctn. Quantity	100
Master Ctn. Dimension	61cm x49cm x 27.5 cm
Master Ctn. Weight	26 Kgs

INSTALLATION

For interconnecting line, only use #14-#18 AWG minimum solid or stranded wire. When being interconnected, maximum wire length between any two is 1500 feet for #18 AWG or 4000 feet for #14 AWG (20 OHMS loop resistance). This smoke alarm can be interconnected with as many as 40 other DC or AC ORIENTALERT smoke alarms and/or heat alarms. Do not connect to any other type or model smoke alarms except the ones we specify.







Xiamen Vs-Top Electronics Co., Ltd.

6th floor, Jinzhongda Park, No.666 Yangguang Road, Xinyang Industrial District, Haicang, Xiamen, China. 361026

Tel: +0086-592-6017700 Fax: +0086-592-6017711 Website: www.orientalert.com