

M-FIRE SL112 Ex

PSL0111

APPLICATIONS: FIREFIGHTING, RESCUE, WORK SAFETY, INDUSTRIAL, OIL & GAS, CHEMICALS

POWER SUPPLY	Li-Ion 2500 mAh			
	LIGHT OUTPUT	RUN TIME	BEAM DISTANCE	PEAK BEAM INTENSITY
HIGH	222 lm	4 h 15 min	432 m	46 664 cd
MEDIUM	69 lm	14 h	270 m	18 228 cd
LOW	11 lm	82 h 10 min	110 m	3028 cd
DIMENSIONS	256 x 136 x 170 mm			
WEIGHT	700 g, 1050 g (product + charger)			
THE SET INCLUDES	shoulder strap, charging base			

IP54 RATING 1 m IMPACT RESISTANCE

ATEX No.: Ex I M1 EX IA I MA / Ex II 1G EX IA
OP IS IIC T4Ga Sira 17 ATEX 2195X

ANSI FL1 STANDARD * 222 lm ◀ 432 m



M-Fire SL112 Ex is an advanced searchlight certified by ATEX for use in explosion-hazard zones [Zone 0]. It emits a 222-lumen beam that illuminates areas up to 432 meters away, making it essential for operations in dense smoke and challenging conditions. The flashlight offers three modes, with a runtime of up to 82 hours in Low mode. Its IP54 rating ensures protection against dust and water splashes, making it durable in demanding work environments. The package also includes a shoulder strap for easy carrying.

PRODUCT MEETS THE FOLLOWING STANDARDS: CE RoHS

MACTRONIC®
VALUE
HIGHLIGHTS

5-YEAR
WARRANTY

PATENTED
DESIGN

ECO FRIENDLY
PACKAGING

