MAGIRUS PORTABLE PUMP FIRE 1500





SERVING HEROES. SINCE 1864.

PORTABLE PUMP FIRE 1500 TECHNICAL DATA

<u>OUTPUT</u>

/ At 3 m suction height/ At 7.5 m suction height

1,500 l/min at 10 bar 750 l/min at 10 bar

CHARACTERISTICS

- I High performance, water-cooled 4-cylinder straight FPT engine, operates very smooth and vibration-free
- / 1,368 ccm and 57 kw (77 hp) at 6,000 rpm
- Fuel tank size 181
- *I* Two-stage centrifugal pump resistant to dirty water, dry running, water hammers and temperature fluctuations
- / Pump made of corrosion-proof light alloy, pump shaft made of stainless steel
- / Magirus PRIMATIC pump self-priming system
- / Closing pressure: 17 bar
- / Weight: 196 kg (ready for use)
- / Dimensions (L x W x H): 1,092 x 749 x 842 mm

ADVANTAGES AND BENEFITS

- / Maximum performance in permanent operation with up to 8 m suction height for maximum safety during operation
- I Stable and light stainless steel frame suitable for carrying harness attachments e.g. for helicopter transport
- / 8 x ergonomic hand grips on all sides allowing a safe and quick transport
- I Anchoring bores in frame in line with EN standards ensure fire pump fixation, no matter on which vehicle type
- / Dimensions according to EN norm 14466
- I Electric starter as standard, including manual start device
- Intuitive HMI panel with all functions in one position for easy operation

SELF-PRIMING SYSTEM MAGIRUS PRIMATIC

- I Fully automatic working priminig system for Magirus fire pumps
- / Particularly safe to operate with low-wear properties
- I Design based on double acting membrane pump, which is particularly resistant to dirt
- *I* System is switched on and off directly by pump pressure, w/o additional electrical, hydraulic or other systems
- *I* Two independently working membrane pump units active during the priming phase, but off-line while water is being pumped
- / Robust design and corrosion-resistant materials guarantee long-term use

OPTIONALLY AVAILABLE


- / Different coupling types
- Battery charger
- / Different type power sockets for charging



Ergonomic storage device



Easy to use, intuitive operation



Schematic drawing of the Magirus priming system

Illustrations may include additional options. We reserve the right to make technical changes or improvements at any time without prior notice. Errors and omissions excepted.

MAGIRUS GmbH • Graf-Arco-Straße 30 • 89079 Ulm • Germany www.magirusgroup.com • magirus@cnhind.com