


OASiS

So much more than a wireless alarm system



Make your premises
an oasis of security

AN OASIS UNDER YOUR ROOF

A WIRELESS SOLUTION FOR THE 21ST CENTURY

- ✓ Easy installation gentle to interior furnishing and decoration
- ✓ A Lego-like architecture for tailoring the system to your needs
- ✓ Reliable and easy to operate
- ✓ An EN50131 grade 2 system
- ✓ 3 year battery lifetime
- ✓ 5 year warranty

up to 32

motion



window opening




door opening



internal siren



door bell



control panel



outdoor keypad



door lock interface



keypad



proximity user cards and tags



key fobs



Optional equipment for remote access and reporting:

- ✓ LAN (Ethernet) & PSTN phone line communicator
- ✓ GSM / GPRS communicator voice message alarm-reporting phone line communicator

System operational capability:

- ✓ up to 30 proximity user cards
- ✓ up to 30 PIN codes (codes and cards can be combined for higher security)
- ✓ up to 16 key fobs

detectors



re



glass breaking



gas
leakage



panic
button



remote
listening &
talking



outdoor
siren



appliance
control
(heating,
lights,
curtains,...)



room
thermostat



garage door
opening

car
protection



Wireless for simplicity


Oasis uses the latest **868 MHz** narrow-band communication protocol. **Working range up to 600 meters** (in an open area). All wireless communication is tested regularly.

Forget about battery replacement

Devices are powered by 3 V lithium batteries which provide **energy for at least 3 years** of normal operation. Oasis checks the batteries and informs you when it is time for replacement.

The control panel can:

- ✓ be operated remotely by phone or Internet
- ✓ report selected events by SMS to your phone
- ✓ report all details to a central monitoring provider



Oasis is not only capable of securing your house, but also **your car** standing by your house or in your garage (just press arming button A on the keypad after parking). A tiny RC module can also be fitted to your car to open the garage or gate just by flashing headlights or blowing the horn.

Your mobile phone can also be used to **remotely control other appliances in the house** (heating, curtains, lights.), either by SMS commands or even charge free just by dialing from your number.

JA-80 OASIS SYSTEM DEVICES

JA-80K control panel



up to 32 detectors, 16 key fobs, 30 user codes (cards). Allows 2 level partial arming (or 2 partition splitting). Mains powered with backup battery. Records 127 latest events incl. date and time. Provides internal & external audible warning and 2 programmable outputs. Remote access and reporting can be provided by PSTN, GSM or LAN optional modules.

JA-85B glass break det.



dual technology sensor can recognize glass breaking in a radius of 9 meters. Digital signal processing provides high immunity to false signals. Can also be installed in a car.

TP-80 room thermostat



it can wirelessly control a heater via an AC module to achieve desired temperatures. It also allows the heating to be remotely controlled by mobile phone.

JA-82M window detector



an invisible magnetic sensor to indicate a Euro-standard window opening. Can be installed into the most up-to-date window frames.

JA-80H outdoor keypad



has a built-in RFID card reader, allows entrance door opening and can also be an external bypass switch. Connected to the control panel by cable via the WJ-80 interface.

JA-80F keypad



allows system control and programming. Has a built-in RFID card reader. Indicates current window or door status (opening). The **JA-80E** is a hard wired option.

JA-80L internal siren



mains powered siren to sound alarms, exit and entrance warnings, door bell signals and detector triggered chimes. Signals a tamper if disconnected (thief verification).

WJ-80 interface



connects outdoor keypad to the control panel cable and provides an output signal (power) to open an electric door lock. Connection of 3rd party keypads possible (Wiegand protocol).

JA-80P motion detector




PIR sensor covers up to 112 square meters (pet zone lens optional). Digital signal processing provides a high immunity to false signals. Can also be used to detect a door opening.

JA-80A outdoor siren



totally wire-free siren in a robust housing. Serves also as a front-line alarm tampering detector. Its lithium battery lifetime is from 3 to 5 years (depends on alarm rate).

UC-82 output module



provides 2 radio controlled relays switchable by control panel, RC remote controls or wireless detectors. Needs 12VDC. **AC-82** is a mains powered option.

JA-80PB combined detector



dual technology motion PIR/glass break sensor combination. Digital signal processing provides high immunity to false signals.

RC-80 key-fob



can set, unset and trigger panic alarms. Can also operate other devices (via UC and AC modules). An optional cover allows selection of 2 or 4 buttons.

JA-80V LAN module



a communicator combining LAN (Ethernet) and PSTN tel. line. Allows remote access by mobile phone or Internet. Reports to a monitoring station or cell phone.

JA-80M door detector



magnetic sensor senses door (or window) opening. Provides an input for external wired sensors.

RC-88 wall button



can serve as a wire-free panic trigger or as a remote control for arming. Can also operate UC and AC modules or the JA-80L door bell function.

JA-80Y GSM module



a communicator using a GSM network. Allows remote access by mobile phone or Internet. Can report to a monitoring station or a cell phone. Provides a GSM gateway.

JA-80S fire detector



combines an optical smoke sensor with a heat sensor. Has a built-in siren for local audible warning and a self testing feature.

RC-89 door bell button



can be used as a wire-free door bell button with a JA-80L but it can also serve as a hidden panic trigger or a remote control for UC and AC modules.

JA-80X voice module



reports alarms via voice messages and a PSTN telephone line. Up to 6 messages can be recorded and reported to up to 4 tel. numbers.

JA-80G gas detector



indicates combustible gas or vapour leakage. Based on a platinum filament sensor. This detector is mains powered.

RC-85 remote control



this module can be easily installed in a car to operate devices by flashing lights or using a horn. Can open a garage door, parking gate, lights etc. Powered by the car.

SP-02 speaker phone



when connected to a PSTN phone line (or 80Y GSM gateway) it allows authorized numbers to call in to listen and talk (for alarm verification).

JA-85P motion detector



mini-size PIR sensor, suitable to protect a small room or a car interior. Digital signal processing provides high immunity to false signals.

PC-01 proximity card



up to 30 cards (or **PC-02** key tags) can be enrolled to operate the system. The card can also be combined with a four digit PIN for higher security.

JA-80T interface cable



allows the control panel to be connected to a PC's USB port. Suitable for installers and users who want to supervise the system by **ComLink** software.

Distributed by:

Manufactured by:

Jablotron s. r. o.

Pod Skalkou 33, 466 01 Jablonec nad Nisou

Czech Republic, tel.: +420 483 559 911

www.jablotron.com