

## Foam Making Equipment

The foam inductors are designed to feed foam concentrates at a set mixing rate into the hose line. Inductors are placed in the delivery line between the pump and the foam nozzle and can be used for medium- and also for heavy foam nozzles. The venture system creates a vacuum in the body of the inductor and the foam concentrate is picked up via a suction hose ND 19 with a Storz D 25 coupling. At the foam inlet Storz D 25 adapters are generally mounted. A mixing rate between 0% and 6% is possible. AWG-Foam inductors are also available with an individual foam pickup rate on request.

- Aluminium alloys (A)
- Copper alloys (C)

### High pressure inductor PN 40 adjustable for water and foam liquid, self-priming



3505

To be mounted directly in the supply line between the high pressure pump and the hosereel. No by-pass installation required. Switch-over to water or foam operation possible. Bore of the water supply line is not reduced. Handle used to switch over to foam. Admixing rate adjustable between 0 - 6%. An installed non-return valve prevents backflow of the premix to the pump.

#### Thread Connection

In- and outlet thread	Mixture flow rate (l / min)	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Ident-No.	Remarks	Alloy
2 x G 1 A	80	200	155	120	3,600	30369193		C
2 x G 1 A	150	200	155	120	3,600	30373093		C