





TRELLCHEM® SPLASH 900



Splash 900

Full-body splash protection for use by both emergency back-up teams and industrial use where a gastight suit is not required, yet still good protection is needed. Provides specially good protection against acids and alkalis. Designed to carry a breathing apparatus outside the suit. Trellchem* Splash 900 is fully certified in accordance with the European standard EN 14605.

GARMENT MATERIAL

The Trellchem® Splash 900 material is made from a strong and flexible polyamide fabric, which is single coated with yellow PVC. This construction provides a soft and durable material with good resistance to a wide range of industrial chemicals. There is an option for double coated fabric. Both fabrics are antistatic to EN 1149-5.

COLOR

Yellow (standard material).

STANDARDS

- EN 14605, type 3 ("liquid tight")
- EN 14126 (infective agents)
- EN 1149-5 (antistatic suit material)
- Approved for use in explosive environments,
 Zones 1, 2 / 20, 21, 22 only and Group IIA, IIB, according to ATEX Directive 94/9/EC





THE SAFETY STANDARD

TRELLCHEM® SPLASH 900



Splash 900 face seal



Splash 900 with attached PVC safety



The Splash 900 has a long watertight PVC zipper, which is placed on the back, across the shoulders.

DESIGN

Non-encapsulating design with face seal and without hump, BA worn outside the suit.

FACE SEAL

The rubber face seal is anatomically designed for optimum safety and comfort. It provides the user with a tight, yet perfectly comfortable fit around the face. Option: Attached mask (possible only with some mask types).

ZIPPER

Watertight PVC zipper placed horisontally on the on the back, across the shoulders, for easy donning. The zipper is protected by a splash guard (flap).

GLOVES & ATTACHMENTS

Butyl rubber gloves as standard. The gloves are attached with the Trellchem® Bayonet glove ring system, which offers quick and simple glove exchange. Option: Chloroprene rubber, PVC or Viton®/Butyl rubber gloves.

FOOTWEAR

Attached yellow PVC safety boots, alternatively socks or open double legs. Option: Nitrile rubber/Firemen's boots.

REINFORCEMENTS

For extra durability, the suit is fitted with reinforcements on elbows and knees.

SEAM

Double welded seams.

Trellchem* is a registered trademark owned by Trelleborg AB. Viton* is a registered trademark owned by DuPont Perfomance Elastomers L.L.C. ©2015 Ansell Limited. All Rights Reserved.

