

Top-of-the-line gas-tight and warfare agents protection

- Well-proven design that fits on top of all major SCBA brands and bottle sizes
- Offers outstanding permeation times - tested for 24 hours
- High-level protection, ensuring wearer confidence
- Patented fabric system with antistatic butyl rubber and chemical and degradation resistant Viton® rubber on an aramid base fabric
- Meets NFPA 1991:2016 including the optional chemical flash fire and liquefied gas protection requirements
- PyroMan™ tested
- Approved for work in explosive atmospheres



CV wide vision visor with 3D depth of 20 cm, giving extra side view. Alternatively large VP1 visor.



Bayonet glove ring system for quick and simple glove exchange



Strong and flexible suit material which offers maximum protection against aggressive chemicals in all forms



Sewn-in socks in the suit material or attached boots



Gas-tight Protection




Re-usable

Applications

- Chemical Handling
- Emergency Teams
- Fire & Rescue Service
- First Response
- Hazmat Teams
- Industrial and Tank Cleaning
- Law Enforcement
- Petrochemicals

Material Construction



PRODUCT INFORMATION

	AlphaTec® EVO TYPE CV/VP1
Design	<ul style="list-style-type: none"> • Encapsulating design type CV (with visor and hump, BA worn inside the suit) • Encapsulating design type VP1 (larger visor, with hump, BA worn inside the suit)
Garment material	Outer: Strong, flexible and flame retardant aramid fabric coated with antistatic butyl rubber and an additional top layer of Viton® rubber. Inner: Chloroprene rubber and a multilayer barrier laminate.
Seams	Stitched with aramid thread for superior strength and durability. Covered on the outside with a Viton® rubber tape and on the inside with a welded-on barrier laminate tape.
Visor	<ul style="list-style-type: none"> • Made from a rigid 2 mm impact and chemical resistant PVC • Comes in two optional sizes; CV or the larger VP1 • Covered by a replaceable, antistatic Tear-off/ATEX lens
Gloves & Attachments	2-part system with Ansell Barrier® #02-100 inner glove and AlphaTec® #38-628 Viton®/Butyl rubber glove. The gloves are attached with a Bayonet glove ring system, which offers quick and simple glove exchange. NFPA 1991 certified suits have a 3-part glove system with the above plus the AlphaTec® #58-800 Overglove for additional cut protection.
Footwear & Attachments	Sewn-in socks/booties made of the suit material. Alternatively attached black nitrile rubber safety boots with European approval as Firemen's boots. The boots are fixed with an ergonomically designed ring attachment, for simplified boot exchange. NFPA 1991 certified suits have sewn-in socks.
Zipper	AlphaTec® HCR zipper, which includes a barrier film for increased chemical resistance. The zipper is closing downwards, for added safety, and is protected by a flap/splash guard.
Ventilation	A ventilation system is included as standard. For the safety of the wearer, it provides a constant level of overpressure inside the suit. The AlphaTec® Regulating valve MkII has 3 ventilation rates (2, 30 and 100 l/min) plus zero/off position. CEJN 221 male coupling for connection to the SCBA (requires separate connection hose). Two overpressure valves in the back of the hood.
Colour	Red or olive green.
Sizes	XXS - XXXL
Included with each delivery	<ul style="list-style-type: none"> • 1 pce inside hump protective foam • 1 pair of cotton comfort inner gloves • 2 pcs extra locking pins for the Bayonet glove ring system • 1 pce Molycote lubrication for the O-rings in the Bayonet glove ring system • 1 pce grease stick for lubrication of the zipper • 1 pair of comfort silicone oversocks (only for suits with sewn-in socks) • 1 pce coat hanger • 1 pce AlphaTec® storage bag
Optional accessories	<ul style="list-style-type: none"> • Combined Regulating valve & Airline passthrough MkII • Anti-fog lens • Hands-free visor light system • Internal waist belt & leg shortener for size adjustment • Manometer holder and inside pockets & loops for radio, PTT etc. • D-ring for holding small measuring instruments & tools • Customised marking, e.g. digits, letters, logos • AlphaTec® #58-800 Overglove for improved cut & puncture resistance • Other accessories are available upon request
Standards & Approvals	<ul style="list-style-type: none"> • NFPA 1991:2016 incl. the optional Chemical Flash Fire & Liquefied Gas protection requirements* • EN 943-1:2015 and EN 943-1/FprA1:2018 • EN 943-2:2002 and FprEN 943-2:2018 • EN 1073-2:2002 (radioactive particle protection) • EN 14126:2003 (infective agent protection) • EN 1149-5:2008 (antistatic suit material) • Approved for use in ATEX zones 0, 1, 2/20, 21, 22 and chemical group IIA, IIB, IIC <p>* Only encapsulating suits with sewn-in socks/booties.</p>

For additional information, visit us at protective.ansell.com or contact us at:

Ansell Protective Solutions AB
Arenagatan 8B
215 33 Malmö
Sweden
Tel. + 46 10 205 1800
order.protective@ansell.com

North America
Ansell Healthcare LLC
111 Wood Avenue South, Suite 210
Iselin, NJ 08830, USA
Tel. + 1 800 800 0444
Fax. + 1 800 800 0445
info@ansell.com

Europe, Middle East and Africa
Ansell Healthcare Europe NV
Riverside Business Park
Blvd International, 55
1070 Brussels, Belgium
Tel. + 32 2 528 74 00
Fax + 32 2 528 74 01
info.europe@ansell.com

Asia Pacific
Ansell Protective Solutions Singapore Pte. Ltd.
237, Pandan Loop,
#05-05 Westech Building
128424 Singapore
Tel. + 65 6908 4115
order.protective@ansell.com

Latin America & Caribbean
Ansell Brazil Ltda.
Rua das Figueiras 474 – 4º Andar
Bairro Jardim
SP 09080-300 Santo André, Brazil
CNPJ: 03.496.778/0001-21
+55 11 3356 3100
sac@ansell.com

Performance Standards



TYPE 1a-ET



EN 1073-2



EN 14126



EN 1149-5

EN 1149-5:
This applies
only to the
suit material.