

Handline Nozzle

Style #368

- Constant flow selectable gallonage nozzle with multi flow settings
- Selected flow remains constant regardless of pattern change
- Multi pattern detents for positive positioning of pattern
- Combination of fog and straight stream
- Superb wide fog pattern for optimum personal protection
- Flush without shutting down
- Standard optimum operating pressure 100 psi (7bar)
- Excellence performance at pressure as low as 50 psi (3.5 bar)
- Conforms to all aspects of NFPA 1964 (Spray nozzles, shutoff and tips) 2003 edition

PROTEK
NFPA1964
COMPLIANT



Raised lug for flashover fog pattern



Newly improved handle with two reinforced metal pieces on each side to prevent breakage

Specification

Style	Length	Weight (Lbs)	Flow	
			GPM	LPM
368	9.8"	5.5	90-125-150-200-250	360-475-550-750-950

UNIQUE FEATURES ON PROTEK NOZZLES



- ① 316 stainless steel spinning teeth ensure corrosion resistance and durability
- ② Raised lug for flashover fog setting
- ③ Laser etched anodized indicating bands for long life and easy use. (No stick labels to fade or come loose)
- ④ Large metal flow select ring (Easy to change flow settings even with a wet glove)
- ⑤ Flush without changing pattern or shutting down
- ⑥ New improved handle with two reinforced metal pieces on each side to ensure breakage free
- ⑦ Stainless steel inlet screen catches solid before they enter nozzle (only things that gets through can be flushed without shutting down)
- ⑧ Heavy duty chrome plated metal shutoff balls ensures a smooth action and long dependable service life
- ⑨ Ergonomic shaped pistol grip for comfort. Pistol grip standard on all models. (Also available in various colors)
- ⑩ Each nozzle etched with a unique series number Aids identification, tracks manufacturing date and warranty
- ⑪ Flow pattern détentes gives positive positioning

Technical Data

Style	Nozzle Pressure		Flow Setting		Actual Flow		Straight Stream Reach			
							Effective		Overall	
	PSI	BAR	GPM	LPM	GPM	LPM	Feet	Meters	Feet	Meters
368	75	5	95	360	82	310	115	35	125	38
			125	475	108	409	125	38	135	41
			150	550	130	492	145	44	155	47
			200	750	173	654	155	47	165	50
			250	950	217	821	160	48	170	51
	100	7	95	360	95	360	140	42	150	45
			125	475	125	475	150	45	160	48
			150	550	150	550	160	48	170	51
			200	750	200	750	170	51	180	54
			250	950	250	950	175	53	185	56
	125	8.5	95	360	106	401	145	44	155	47
			125	475	140	530	155	47	165	50
			150	550	168	636	160	48	170	51
			200	750	224	848	175	53	185	56
			250	950	280	1060	185	56	195	59