

# Ground Monitors

## Unique Features of Protek Ground Monitors

3" waterway with cast vane for flow efficiency

Liquid Filled Pressure Gauge

Fully enclosed worm gear

Dual spring-loaded lock pins for quick and easy break-apart

Carbide Spikes for extended wear

Dual purpose--use as a portable monitor or deck gun

Spring-Loaded forged aluminum folding legs



# #622 Ground Monitor

- Durable, lightweight aluminum construction
- Dual purpose use as a portable monitor or deck gun
- 3" waterway with cast vane for quality stream
- Vertical travel from 80° above to 25° below horizontal with built-in 35° safety stop
- 360° rotation when mounted in the deck mode, 180° in the portable mode
- Compact folding base can be stored in any truck compartment or pre-connected in the hose bed
- Carbide tipped spikes for extended wear and stability
- Fully enclosed worm gear to protect from elements



style #622-2



style #622-1



Direct Mount Flange  
style #190



Quad Stacked Tips  
style #120



Stream Shaper  
style #119



Master Stream Nozzle  
style #847



Self-Educting Nozzle (500 GPM)  
style #887



Self-Educting Nozzle (750 GPM)  
style #888

STYLE	WEIGHT	INLET	OUTLET	FLOW (Ground Mode)		FLOW (Deck Mode)	
				GPM	LPM	GPM	LPM
622-1	28lb	2-1/2,4",5"	2-1/2"	1000	3800	1250	4800
622-2	27lb	(2)2-1/2"	2-1/2"	800	3030	1250	4800