Dual-Purpose Ground Monitors

Se

Style 622-1, 622-2, 622-3

Unique Features of Protek Ground Monitors







Carbide-tipped spike for extended wear resistance

Dual-Purpose Ground **Monitors**



Style 622-1, 622-2, 622-3

- Suitable for use as a portable monitor or a deck gun with features to meet the changing demands of the fire service
- Full 3" waterway for flow rate of up to 1250 GPM (4800 LPM)
- Full 360° rotation in the deck model (Style 622-3), 180° in the portable models (Style 622-1, 622-2)
- Vertical travel of 63° from 12° to 75° above with inbuilt 37° safety stop from 18° to 55° above
- Compact folding base can be stored in any truck compartment or pre-connected in the hose bed
- Carbide-tipped spikes for extended resistance to wear
- Large handle for excellent portability
- Fully enclosed worm gear is protected from the elements
- Available in portable (Style 622-1 and 622-2) or deck-mount (Style 622-3)
- Compatible with a wide range of Protek nozzles and accessories

		Style 622-1	Style 622-2	Style 622-3		
Max. GPM(LPM)		1000 (3800) *	800 (3030)	1250 (4800)		
Inlet	Size	2-1/2" to 5"	2-1/2" (x2)	3"	4"	3"
	Type	Thread	Thread	Flange	Flange	Thread
Outlet		2-1/2"	2-1/2"	2-1/2"		
Control		Single Hand-Wheel	Single Hand-Wheel	Single Hand-Wheel		
Material		Alloy	Alloy	Alloy		
Finish		Red Powder Coating	Red Powder Coating	Red Powder Coating		
Friction Loss		18 psi at 1000 gpm	15 psi at 800 gpm	24 psi at 1250 gpm		
		12 psi at 700 gpm	12 psi at 700 gpm	18 psi at 1000 gpm		
Travel		12 to 75° Vertical	12 to 75° Vertical	12 to 75° Vertical		
		180° Rotation	180° Rotation	360° Rotation		
Weight		32 lbs.	32 lbs.	27 lbs.		

^{*} Maximum flow rate is subject to selection of inlet size

Style 622-3

Fire Fighting Equipment



Style 656









Style 656 shown with Style 622 monitor liftoff



Monitor Nozzle



Style 120 Quad Stacked Tips



Self-Educting Nozzle (500 GPM)



Style 190 Direct Mount Flange



Self-Educting Nozzle (750 GPM)

sales @protekfire.com.tw • www.protekfire.com.tw