## Dual-Purpose Ground Monitors



Style 622-1, 622-2, 622-3
Unique Features of Protek Ground Monitors







Carbide-tipped spike for extended wear resistance

## **Dual-Purpose Ground Monitors**



Style 622-1, 622-2, 622-3

- · Suitable for use as a portable monitor or a deck gun with features to meet the changing demands of the fire service
- Flow rate of up to 1250 GPM (4800 LPM)
- . 3" waterway with cast vane for quality stream
- Full 360° rotation in the deck model, 180° in the portable models
- Vertical travel of 63° from 12° to 75° above with inbuilt 37° safety stop from 18° to 55° above
- · Compact folding base can be stored in any truck compartment or pre-connected in the hose bed
- · Carbide-tipped spikes for extended resistance to wear
- · Large handle for excellent portability
- · Fully enclosed worm gear is protected from the elements
- Available in portable (Style 622-1 and 622-2) or deck-mount (Style 622-3) models
- Compatible with a wide range of Protek nozzles and accessories

		Style 622-1			Style 622-2	Style 622-3		
Max. GPM (LPM)		1000 (3800)			800 (3030)	1250 (4800)		
Inlet	Size	3-1/2"	4"	5"	2-1/2" (x2)	3"	4"	3"
	Type	Thread	Thread	Thread	Thread	Flange	Flange	Thread
Outlet		2-1/2"			2-1/2"	2-1/2"		
Control		Single Hand-Wheel			Single Hand-Wheel	Single Hand-Wheel		
Material		Alloy			Alloy	Alloy		
Finish		Red Powder Coating			Red Powder Coating	Red Powder Coating		
Frition Loss		16 psi at 1000 gpm			15 psi at 800 gpm	24 psi at 1250 gpm		
		12 psi at 700 gpm			12 psi at 750 gpm	18 psi at 1000 gpm		
Travel		12 to 75° Vertical			12 to 75° Vertical	12 to 75° Vertical		
		180° Rotation			180° Rotation	360° Rotation		
Weight		32 lbs.			32 lbs.	27 lbs.		

## Style 622-3







Style 119



Style 656+622





Style 120



(500 GPM)



Style 190



Self-Educting Nozzle

sales@protekfire.com.tw . www.protekfire.com.tw